



AkzoNobel

Material Safety Data Sheet

Date of printing : 8/31/2009.

Date of issue : 8/31/2009

1. Product and company identification

Prepared For
ATTN:
CASCO ADHESIVES
1431 PROGRESS AVENUE

HIGH POINT, NC 27261 US

Prepared by
Akzo Nobel Coatings Inc.
Casco Adhesives
1431 Progress Ave.
High Point, NC 27261 US
(336)841-5111
IN CASE OF EMERGENCY (HEALTH OR SPILLS):
CHEMTREC (US and Canada) (800) 424-9300

Product no. : C9563
Product - Class : Hardener 9563
Customer Part Number :
Customer ShipTo ID : 0000108209

2. Hazards identification

Physical state : Liquid.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Emergency overview : DANGER!
CAUSES RESPIRATORY TRACT, EYE AND SKIN BURNS. HARMFUL IF SWALLOWED. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.
Do not breathe vapor or mist. Do not ingest. Do not get in eyes or on skin or clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

Routes of entry : Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Inhalation : Corrosive to the respiratory system.

Ingestion : Toxic if swallowed. May cause burns to mouth, throat and stomach. Other effects of ingestion may include : burns,

Skin : Corrosive to the skin. Causes burns.

Eyes : Corrosive to eyes. Causes burns. Other effects of eye contact may include : eye damage,

Potential chronic health effects

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Target organs : Contains material which may cause damage to the following organs: skin.

Medical conditions aggravated by over-exposure : pulmonary conditions, skin disorders, eye disorders,

2. Hazards identification

See toxicological information (section 11)

3. Composition/information on ingredients

<u>Name</u>	<u>CAS number</u>	<u>% by weight</u>	<u>Vapor pressure</u>	<u>Exposure limits</u>
formic acid	64-18-6		4.5 kPa (34 mm Hg)	OSHA PEL (United States). TWA: 5 ppm 8 hour(s). ACGIH TLV (United States). TWA: 5 ppm 8 hour(s). STEL: 10 ppm 15 minute(s).
proprietary	-		Not available.	
1,3-benzenediol	108-46-3		Not available.	ACGIH TLV (United States). TWA: 10 ppm 8 hour(s). STEL: 20 ppm 15 minute(s).

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
Eye contact	: Get medical attention immediately if symptoms occur. Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Chemical burns must be treated promptly by a physician.
Skin contact	: Get medical attention immediately if symptoms occur. In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Chemical burns must be treated promptly by a physician.
Inhalation	: Get medical attention immediately if symptoms occur. Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband.
Ingestion	: Get medical attention immediately. Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

5. Fire-fighting measures

Flammability of the product	: In a fire or if heated, a pressure increase will occur and the container may burst.
Flash point	: Closed cup: >93.3°C (>200.0°F)
Flammable limits	: Not available.
Extinguishing media	
Suitable	: Use an extinguishing agent suitable for the surrounding fire.
Not suitable	: None known.
Special exposure hazards	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. UNUSUAL FIRE HAZARDS: During emergency conditions, overexposure to products of combustion may cause a health hazard; symptoms may not be immediately apparent. Obtain medical attention.

5. Fire-fighting measures

Special remarks on fire hazards : Not available.

Special remarks on explosion hazards : Not available.

6. Accidental release measures

Personal precautions : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

7. Handling and storage

Handling : Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Engineering measures : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection Selection of personal protective equipment (PPE) is to be established by the employer performing a PPE hazard assessment. In the U.S.A, OSHA requires completion of a documented PPE hazard assessment as described in 29 CFR 1910.132.

Respiratory : Use properly fitted respiratory protection complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

8. Exposure controls/personal protection

- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eyes** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other protection** : Not available.

9. Physical and chemical properties

- Physical state** : Liquid.
- Burning time** : Not applicable.
- Burning rate** : Not applicable.
- Color** : Not available.
- Odor** : Not available.
- Taste** : Not available.
- Molecular weight** : Not applicable.
- Molecular formula** : Not applicable.
- pH** : Not available.
- Boiling/condensation point** : Not available.
- Melting/freezing point** : Not available.
- Critical temperature** : Not available.
- Relative density** : 1.1
- Vapor density** : Lighter than air
- Volatility** : 62.5% (w/w)
- Odor threshold** : Not available.
- Evaporation rate** : Less than 1. (water) compared with butyl acetate
- Viscosity** : Not available.
- Ionicity (in water)** : Not available.
- Dispersibility properties** : Not available.
- Solubility** : Not available.

10. Stability and reactivity

- Chemical stability** : The product is stable, under normal conditions of storage and use.
- Hazardous polymerization** : Will not undergo hazardous polymerization.
- Conditions to avoid** : No specific data.
Other Conditions to avoid:freezing, light, moisture,
- Materials to avoid** : Reactive or incompatible with the following materials: oxidizing materials, metals and alkalis.
- Hazardous decomposition products** : Not available.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
formic acid	LD50 Oral	Rat	1100 mg/kg	-
	LC50 Inhalation Vapor	Rat	240000 mg/m ³	4 hours
1,3-benzenediol	LD50 Dermal	Rabbit	3360 mg/kg	-
	LD50 Oral	Rat	301 mg/kg	-

Carcinogenicity

11. Toxicological information

Not available.

Mutagenicity

Product/ingredient name

Test

Experiment

Result

Not available.

Teratogenicity

Product/ingredient name

Result

Species

Dose

Exposure

Not available.

12. Ecological information

Data available upon request.





13. Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. Transport information

Note: Information contained in this section may vary from the actual shipping description depending on quantity in containers, mode of shipment and use of exemptions.

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	UN1760	Corrosive liquid, n.o.s. (formic acid)	8	II		RQ: 28602lbs (12971.4kgs) [formic acid]
TDG Classification	UN1760	Corrosive liquid, n.o.s. (formic acid)	8	II		-
IMDG Class	UN1760	Corrosive liquid, n.o.s. (formic acid)	8	II		-
IATA-DGR Class	UN1760	Corrosive liquid, n.o.s. (formic acid)	8	II		-

PG* : Packing group

15. Regulatory information

United States

U.S. Federal regulations : **United States inventory (TSCA 8b)** : All components are listed or exempted.
(HAPS) Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

SARA 313

Form R - Reporting requirements	Product name	CAS number	Concentration
	: formic acid	64-18-6	17.50

15. Regulatory information

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

California Prop. 65

Not applicable.

Ingredient name

Cancer

Reproductive

No significant risk level

Maximum acceptable dosage level

Not applicable.

Canada

Canada inventory : All components of this product are on the CEPA DSL inventory.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

International regulations

International lists

Australia inventory (AICS): Not determined.
China inventory (IECSC): Not determined.
Japan inventory: Not determined.
Korea inventory (KECI): Not determined.
New Zealand Inventory of Chemicals (NZIoC): Not determined.
Philippines inventory (PICCS): Not determined.

** All values in this section reported as percentage by weight, unless otherwise specified.

16. Other information

HMIS III @ Hazardous Material Information System (U.S.A.) :

Health	-	3
Flammability		1
Physical hazards		0
Personal protection		

Caution: HMIS III @ ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risk, and 4 representing severe hazards or risk. Although HMIS III @ ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS III @ ratings are to be used with a fully implemented HMIS III @ program. HMIS III @ is a registered mark of the National Paint & Coatings Association (NPCA).

The customer is responsible for determining the PPE code for this material.

Other special considerations : Not available.

Notice to reader

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.